

Overview	
Dimensions	180 x 109 x 33.8 mm (7.1 x 4.3 x 1.3")
Networking Interface	(1) 2.5 GbE RJ45 port 5G NR and LTE radio
SIM	(1) Nano SIM (1) Nano-SIM or eSIM
PoE Interface	(1) PoE input
Mounting	Desktop stand, wall, window mount (Included)
Tamper Resistance	IK04
Mechanical	
Weight	Device: 410 g (14.5 oz) Stand: 215 g (7.6 oz) Wall mount: 7.6 g (0.3 oz) Window mount: 20 g (0.7 oz)
Enclosure Material	Polycarbonate, aluminum alloy
Mount Material	Polycarbonate, silicone rubber
Hardware	
Management	Ethernet
5G NR	
Category	5G NR
Frequency Bands	n1, n2, n3, n5, n7, n8, n12, n13, n14, n18, n20, n25, n26, n28, n29, n30, n38, n40, n41, n48, n66, n71, n75, n76, n77, n78, n79
Max. TX Power	HPUE power class 2: 26 dBm
4G LTE	
Frequency Bands	B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32, B34, B38, B39, B40, B41, B42, B43, B46, B48, B66, B71
Max. TX Power	HPUE power class 2: 25 dBm

3G UMTS

Frequency Bands	B1, B2, B4, B5, B8, B19
-----------------	-------------------------

Peak Data Speed

5G NSA	Downlink 3.4 Gbps Uplink 560 Mbps
--------	--------------------------------------

5G SA	Downlink 1.8 Gbps Uplink 650 Mbps
-------	--------------------------------------

4G LTE	Downlink 1.6 Gbps Uplink 210 Mbps
--------	--------------------------------------

Antennas

Type	(4) Embedded cellular antennas
------	--------------------------------

Max. Power Consumption	14.5W
------------------------	-------

Power Method	PoE
--------------	-----

Display	1.3" touchscreen
---------	------------------

Buttons	(1) Factory-reset
---------	-------------------

Ambient Operating Temperature	0 to 40 °C (32 to 104 °F)
-------------------------------	---------------------------

Ambient Operating Humidity	5 to 95% noncondensing
----------------------------	------------------------

Certifications	CE, PTCRB, GCF
----------------	----------------

Software

Application Requirements

UniFi Network	Version 10.0.162 and later
---------------	----------------------------